

# TallyGenicom 6600 Series of Line Matrix Printers

the Power  
of



## Technical Specifications

Printer Features	Open	Quiet	Zero Tear	Cabinet	
	6605 Pedestal 6610 6615	6605 Pedestal 6610 6615	6605Z 6610Z 6615Z	6605Q 6610Q 6615Q	6620Q
<b>Standard</b>					
Integrated Print Management	•	•	•	•	•
Ribbon Life Monitor	•	•	•	•	•
<b>Options</b>					
SureStak® Power Stacker					•
Black back forms paper out sensor	•	•	•	•	•
Rear Slide Out Paper Drawer					•
Cabinet Front Access					•
Pedestal Front Paper Tray	•		•		
Pedestal High Rear Paper Tray	•	•	•		
Pedestal Acoustic Shroud	•	Standard			
<b>Physical Size</b>	<b>Height</b>	36" (914.4mm)	36" (914.4mm)	42" (1066.8mm)	40.5" (128.7mm)    40.5" (1028.7mm)
	<b>Width</b>	26" (660.4mm)	26" (660.4mm)	26" (660.4mm)	27" (685.8mm)    27" (685.8mm)
	<b>Depth</b>	21.5" (546.1mm)	25" (635mm)	21.5" (546.1mm)	29" (736.6mm)    33" (838mm)
	<b>Shipping Weight</b>	165 lbs (74.842kg) <i>Not including rear tray</i>	190 lbs (86.182kg) <i>With acoustic shroud</i>	180 lbs (81.646kg)	265 lbs (120.201kg)    300 lbs (136kg) <i>With SureStak Power Stacker</i>
<b>Acoustic</b> (dBA) (per ISO 7779)	6605 - 62	6605 - 58	6605Z - 66	6605Q - 50	
	6610 - 65	6610 - 60	6610Z - 70	6610Q - 50	
	6615 - 68	6615 - 63	6615Z - 70	6615Q - 52	6620Q - 55
<b>shown by Printer models</b>					
	<b>6605</b> <b>6605Q</b> <b>6605Z</b>	<b>6610</b> <b>6610Q</b> <b>6610Z</b>	<b>6615</b> <b>6615Q</b> <b>6615Z</b>	<b>6620Q</b>	
<b>Print Speed</b> (LPM, upper case characters, lower case characters)	<b>High Speed (draft)</b>	500/428	1000/856	1500/1289	2000/1700
	<b>Data Processing</b>	375/300	750/600	1125/900	1500/1200
	<b>Near Letter Quality</b>	200/154	400/306	600/459	800/615
<b>Graphics Speed</b> (Inches Per Minute)	<b>60 x 48 dpi</b>	63	125	187	250
	<b>60 x 72 dpi</b>	42	83	127	167
	<b>90 x 96 dpi</b>	21	42	61	83
<b>Paper Feed Speed</b> (Inches Per Second)	12	20	25	38.5	



# TallyGenicom 6600 Family of Line Matrix Printers

<b>Character Pitch</b>	5, 6, 6.7, 7.5, 8.3, 8.6, 10, 12, 13.3, 15, 16.7, 17.1, 20 (characters per inch)		
<b>Line Spacing</b>	1.5, 2, 3, 4, 5, 6, 8, 9, 10, 12 (lines per inch – plus variable line spacing)		
<b>Graphics Resolution</b>	240 dpi Horizontal, 288 dpi Vertical (max)		
<b>Dot Size</b>	16.7 mil (.42mm)		
<b>Emulations Standard</b>	Tally ANSI, Genicom ANSI, P5000/P600/P6000, Epson FX-1180, IBM Proprinter, MTPL (Tally Dot Matrix), PGL (TG Version), QMS Code V, Tally Industrial Graphics, PCL-3: HP-2564C, DEC LG01		
<b>Character Sets</b>	47 languages and 43 character sets		
<b>Character Styles</b>	Bold, italic, superscript, subscript, underline, overline, strike-through		
<b>Fonts</b>	Draft, Data Processing, Courier, Gothic, OCR A and B		
<b>Barcodes</b>	Code 39, Code 128, Interleaved 2 of 5, UPC-A, UPC-E, EAN 8, EAN 13, EAN 128, Codabar, MSI, PDF-417, Postnet, Intelligent Mail Barcode (IMB)		
<b>Printer Software</b>	TallyGenicom PrintNet Suite of Tools - remote management software suite - included with the Ethernet option		
<b>Printer Drivers</b>	Win 7, Vista, XP, Windows 2000, Server 2003, Server 2008, Server 2008r2, Linux, Unix, AIX, SAP		
<b>Environmental Advantages</b>	ENERGY STAR® qualified, lower consumable materials and packaging, improved handling of recycled paper, faster power-up from sleep mode than laser printers		
<b>Genuine TallyGenicom Cartridge Ribbons</b>	Standard Life	17,000 pages	
	Extended Life*	30,000 pages	*Not compatible with 500 LPM printer models
<b>Paper Path/Handling</b>	Straight paper path with easy-load adjustable tractors, paper-out detection and alarm, paper-motion detection and alarm		
<b>Paper Type</b>	Continuous, fan folded, edge-perforation		
<b>Print Width</b>	13.6" (345mm)		
<b>Media Width</b>	3" (76mm) to 17" (432mm)		
<b>Media Copies</b>	Up to 6 parts		
<b>Media Weight</b>	15 to 100 lbs up to 0.025" thickness 56 to 163 gm/m <sup>2</sup> up to 0.64mm thickness		
<b>MTBF*</b>	10,000 hours at 25% duty cycle and 25% page density (*Mean Time Between Failures)		
<b>Interfaces</b>	Serial – RS-232 Parallel – IEEE-1284/Centronics Ethernet – PrintNet Suite 10/100 Base T (optional) Auto Switching – Between active ports		
<b>Power Voltage</b>	AC input range 88-270 VAC, 45 to 65 HZ		
<b>Power Wattage (ENERGY STAR)</b>	Less than 14 Watts in energy saving mode		
<b>Power Wattage (typical)</b>	6605/6605Q/6605Z	175 Watts	6615/6615Q/6615Z 390 Watts
	6610/6610Q/6610Z	260 Watts	6620Q 475 Watts



© 2011 Printronix, Inc. All rights reserved. Genicom, Tally, TallyGenicom, TG TallyGenicom, the TG Logo, Intellifilter, Intelliprint, PrintNet Suite, PrintNet Enterprise, PrintNet, Smart Ribbon and Printronix are trademarks or registered trademarks of Printronix, Inc. All other trademarks, product names, company names or logos herein are the property of their respective owners. Product appearance and/or specifications are subject to change without notice.  
Printed in USA. PTX\_602A(4/11)



14600 Myford Road, Irvine, CA 92606  
1-800-665-6210 • www.tallygenicom.com