

T2240 Serial Matrix Printer

Rugged, Fast and Affordable



Fast and Affordable.

Rugged, fast and affordable, the T2240 is built to handle multi-part forms with ease. Specially engineered "flat" push tractors drive forms through an uncommonly straight paper path for jam-free operation. With accessible, front-load tractors and a platen knob to facilitate forms adjustment, paper loading is quick, and down time minimal.

The T2240 industrial strength forms printers deliver versatile transaction printing in no time, every time. Versatile Configuration. Depending on your specific needs, there is a configuration exactly suited for you.

Ideal For Many Markets & Applications.

Federal, State & Local Government - Print tax forms, payroll checks, expense reports, inventory reports, invoices.

Manufacturing, Transportation, & Distribution - Print pick lists, shipping labels and freight bills. Excellent readability on all industry standard bar codes, including POSTNET. Energy Star compliant and low-cost to own and operate.

Healthcare - Handles a wide variety of media including bar code labels for patient charts, prescription labels, pre-printed forms for billing departments. High reliability ensures accurate patient information with 24-wire print quality.

- Print speeds up to 500 characters per second at 12 CPI!
- 10,000 pages per month workload.
- 24-pin configurations produce letter-quality print.
- 80-column (small footprint) or 136-column configurations available.
- Straight paper path means jam-free operation.
- Up to 6-part forms.
- Front load single sheet feed standard; optional 150 page sheet feeder.
- Zero tear-off means no wasted forms.

Available Configuration:

T2240/9 - 500 CPS Printer, 9 Wire, 80 Column, Parallel

T2240/24 - 440 CPS Printer, 24 Wire, 80 Column, Parallel

Features & Specifications

Print Speed	9 wire Printhead: At 10, 12 cpi: Draft: 413, 500 Copy/Draft: 310, 310 NLQ: 77, 77; 24 wire Printhead: At 10, 12 cpi: Draft: 409, 440 Copy/Draft: 275, 330 LQ: 92, 110
Print Method	Serial Impact, 80 columns.
Resolution	9 wire: 144 X 240 DPI. 24 wire: 360 X 360 DPI.
Character Density	10, 12, 15, 17.1, 20 cpi + Elongated
Line Density	2, 3, 4, 6, 8, 12 lpi
Character Sets	256 characters, 20 international sets, IBM PC® and Epson®
Printhead Life	300 million
Standard Connectivity	Bi-directional Centronics Parallel, 64K interface buffer
Optional Connectivity	RS232 Serial, RS422 Serial, TallyCom+ 10/100BaseT External Print Server
Standard Emulation	9-wire: MTPL*, IBM® Proprinter XL, Epson® FX850+/FX1050+. 24-wire: MTPL*, IBM® Proprinter XL24e, Epson® LQ850+/LQ1050+ /EscP
Fonts	9-wire: Draft, Copy Draft, Courier, Quadrato, OCR A & OCR B, Bar Code + LCP. 24-wire: Draft, Copy Draft, Courier, Roman, San Serif, Prestige, Script, OCR A & OCR B, Bar Codes + LCP
Consumables	4 million characters
STD Paper Handling	Flat push tractors (front/bottom), straight path for continuous forms and labels, auto paper load, auto quick tear, auto view, paper advance knob
Opt'l Paper Handling	push tractor, automatic sheet feeder
Number of Copies	9-wire: 1 + 5; 24-wire: 1 + 3
Paper Type	Continuous, Cut Forms (optional feeder)
Paper Weight	NA
Paper Size	Width: 3-10"; Length: continuous Forms 3"-22", Cut Forms 3"-14"
Physical Weight	17.6 lbs
PhysicalSize	19" x 9.7" x 7.9"
Power Voltage	AC 120V +/- 10% OR AC 220V - 240V +/- 10%
Power Frequency	60Hz OR 50Hz
Power Consumption	50 watts (operating)
Compliance	Energy Star compliant, Ozone-free.
Workload	Up to 10,000 pages per month
Reliability MTBF	12,500 hours @ 100% duty cycle
Drivers	Windows 95/98/Me, NT 4.0, 2000, XP; SAP
Temperature	NA
Humidity	NA
Acoustic	53 dB (A) LQ
Warranty	Two Years Return To Depot
Option 1	second front push tractors; front automatic cut sheet feeder
Option 2	RS-232 Serial Interface; RS-422 Serial Interface; TallyCom+ 10/100BaseT External Print Server
Option 3	Printer Stand; Paper Basket; Castors
Note	Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Printed Date: 04/22/2007 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100
Chantilly, VA 20151
T 800.436.4266
www.tallygenicom.com

