

## LA550 Serial Matrix Printer

Fast, high-quality flexible printing optimized for your Compaq® environment.

### Dependable class-leading performance

The dependable LA550N and LA550W offer class-leading performance. Flat push tractors drive forms through a straight paper path, resulting in delivery of invoices, shipping bills, labels, and statements time after time. At up to 750 characters per second and with workloads to 26,000 pages per month, the LA550N and LA550W are ideal for tough, transaction printing. The LA550N and LA550W can be optionally configured with up to three input tractors.



From the small 80-column footprint of the LA550N to the 136-column capacity of the LA550W, their rugged design and quiet operation equip them for the warehouse, the shipping dock or the front desk. Back room durability combined with front-office 24-wire print quality and a variety of automated performance features make the LA550N and LA550W a serious solution for demand document pricing.

### Versatile Forms Handling

The LA550 printer loads up to three forms at once, using a straight paper path for jam-free operation. You can load up to 6-part forms on front tractors, and it includes automatic gap adjustment and quick-tear for ease of use. Plus, our control panels are simple to operate, and the Paper park is designed for easy switching between forms.

- Print speeds up to 750 characters per second
- 26,000 pages per month workload
- 80-column (small footprint) or 136-column configurations
- 15 industry standard bar codes resident including POSTNET
- 24-pin print head produces excellent print quality
- Versatile forms handling
- Simple to operate control panel

## Features & Specifications

<b>Print Speed</b>	At 10,12,15 cpi; Draft: 500, 600, 750; NLQ: 180, 220, 135; LQ: 90, 110, 135
<b>Print Method</b>	Serial Impact Dot Matrix (Bi-directional)
<b>Resolution</b>	graphic resolution maximum: 360 x 360 dpi
<b>Throughput</b>	430 pph (ECMA 132, draft)
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Line Density</b>	2, 3, 6, 8, 12 lpi
<b>Character Sets</b>	256 characters, 20 international sets, IBM PC® and Epson®
<b>Standard Connectivity</b>	Bi-directional Centronics Parallel and RS-232 Serial (auto-switching), DEC MMJ adapter included. 64K buffer.
<b>Optional Connectivity</b>	RS-422 Serial
<b>Standard Emulation</b>	DEC ANSI PPL2, IBM® Proprinter XL24, Epson® ESCP/2
<b>Fonts</b>	Draft, Copy Draft; NLQ and LQ: Courier, Roman, San Serif, Cyrillic, OCR A/B, 15 Bar codes & scaleable LCP font (Accepts downloadable fonts in Epson® and IBM® XL24 format); Bar Codes: Code 2/5, Code EAN 8, Code EAN 13, Code UPCA, Code UPCE, Code Delta-Distance; Code 39, Codabar, Code BCD matrix, Code 11, Code MSI/modified Plessey, Code 128, & Code 128 EAN, POSTNET, LCP
<b>Consumables</b>	LA550N 3.6 million characters, LA550W 5.0 million characters
<b>STD Paper Handling</b>	Friction and push tractor, front feed (straight path for continuous forms and labels), auto paper load, auto quick tear, auto view, full paper parking, auto-gap adjustment (for forms thickness)
<b>Opt'l Paper Handling</b>	Supplemental push tractors (front and/or rear)
<b>Number of Copies</b>	Orig. +5 (front push tractors) without jamming; 3 forms at once and autoswitch between forms without operator intervention
<b>Paper Type</b>	Continuous feed, manual single cut sheet (front insertion)
<b>Paper Weight</b>	NA
<b>Paper Size</b>	LA550N: 3"- 10" width; 3" - 22" length; LA550W: 3" - 16.5" width; 3" - 22" length
<b>Physical Weight</b>	LA550N: 29 lbs; LA550W: 35 lbs
<b>Physical Size</b>	LA550N: 16.7" x 11.8" x 15.7"; LA550W: 23.6" x 11.8" x 15.7"
<b>Power Voltage</b>	120V or 220-240V
<b>Power Frequency</b>	60 Hz or 50 Hz
<b>Power Consumption</b>	40 watts (operating); 15 watts (standby)
<b>Compliance</b>	Energy Star compliant, Ozone-free.
<b>Workload</b>	Up to 26,000 pages per month
<b>Reliability MTBF</b>	10,000 hours @ 100% duty cycle
<b>Drivers</b>	Windows 95, 98, 2000, XP, NT 4.0
<b>Temperature</b>	+10°C to +35°C
<b>Humidity</b>	20% - 80% (relative humidity)
<b>Acoustic</b>	53 dB (A)
<b>Warranty</b>	One Year Return To Depot.
<b>Option 1</b>	Supplemental push tractors, Ethernet 10/100.
<b>Note</b>	Parameter Selections: Front panel menu (32 character LCD) and host programmable (3 separate menu configurations can be stored for access through the interface). Exceeding the monthly duty cycle will not void the warranty if TallyGenicom consumables and maintenance kits are used.



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Printed Date: 04/22/2007 Copyright © 2006 TallyGenicom, L.P.

4500 Daly Drive, Suite 100  
Chantilly, VA 20151  
T 800.436.4266  
www.tallygenicom.com

